

WO 03/039053

PCT/US02/35285

RECEIVED
CENTRAL FAX CENTER

APR 22 2005

1 36. The storage medium of claim 21, said network management
2 process further comprising, in response to a quality of
3 data transmitted to the client below a standard, the step
4 of relocating the client.

1 37. The storage medium of claim 36, wherein the step of
2 relocating the client in said network management process
3 further includes the steps of:
4 identifying a parent of the client as a marked node; and
5 searching a new spot for the client, the new spot not
6 being a child of the marked node.

1 38. The storage medium of claim 37, wherein the step of
2 relocating the client in said network management process
3 further includes the steps of:
4 in response a sibling of the client having a capacity for
5 the client, connecting the client as a child of the
6 sibling; and
7 in response to the sibling not having the capacity for
8 the client, directing the client to the data stream
9 source.

1 39. The storage medium of claim 38, wherein the step of
2 relocating the client in said network management process
3 further includes the step of recursively searching the
4 new spot for the client in the hierarchy structure.

1 40. The process of claim 36, said network management process
2 further comprising the step monitoring a jitter of a data
3 stream transmitted to the client.

WO 03/039053

PCT/US02/35285

1 41. A network data transmission system (100), comprising:
2 a content provider (101);
3 a plurality of clients seeking data from said content
4 provider (101); and
5 a client connection manager (105), said client connection
6 manager (105) arranging said plurality of clients
7 in a hierarchy tree structure (102) having a first
8 client (112) of said plurality of clients coupled
9 to said content provider (101) as a node in a first
10 tier of the hierarchy tree structure (102) and at
11 least a portion of remaining clients of said
12 plurality of clients as a descendent of the first
13 client (112).

1 42. The network data transmission system (100) of claim 41,
2 the first client (112) receiving data from said content
3 provider (101) and relaying the data to the descendent
4 thereof.

1 43. The network data transmission system (100) of claim 42,
2 said plurality of clients further including a second
3 client (122), the second client (122) being a child of
4 the first client (112) in the hierarchy tree structure
5 (102) and receiving the data from the first client (112).

WO 03/039053

PCT/US02/35285

1 44. The network data transmission system (100) of claim 43,
2 said plurality of clients further including a third
3 client (132), the third client (132) being a child of the
4 second client (122) in the hierarchy tree structure (102)
5 and receiving the data from the second client (122).

1 45. The network data transmission system (100) of claim 43,
2 said plurality of clients further including a third
3 client (124), the third client (124) being a child of the
4 first client (112) and a sibling of the second client
5 (122) in the hierarchy tree structure (102) and receiving
6 the data from the first client (112).

1 46. The network data transmission system (100) of claim 41,
2 said plurality of clients further including a second
3 client (116) coupled to said content provider (101) as a
4 node in a first tier of a second hierarchy tree structure
5 (106), the second client (116) receiving data from said
6 content provider (101).

1 47. The network data transmission system (100) of claim 46,
2 said plurality of clients further including a third
3 client (126), the third client (126) being a child of the
4 second client (116) in the second hierarchy tree
5 structure (106) and receiving the data from the second
6 client (116).

WO 03/039053

PCT/US02/35285

- 1 48. The network data transmission system (100) of claim 47,
2 said plurality of clients further including a fourth
3 client (136), the fourth client (136) being a child of
4 the third client (126) in the second hierarchy tree
5 structure (106) and receiving the data from the third
6 client (126).
- 1 49. The network data transmission system (100) of claim 47,
2 said plurality of clients further including a fourth
3 client (128), the fourth client (128) being a child of
4 the second client (116) and a sibling of the third client
5 (126) in the second hierarchy tree structure (106) and
6 receiving the data from the second client (116).
- 1 50. The network data transmission system (100) of claim 41:
2 said client connection manager (105) arranging said
3 plurality of clients into the hierarchy tree
4 structure (102) in response to data transmission
5 capacities of said content provider (101) and said
6 plurality of clients; and
7 said client connection manager (105) dynamically
8 adjusting the hierarchy tree structure (102) in
9 response to a data transmission quality in the
10 hierarchy tree structure (102).

WO 03/039053

PCT/US02/35285

1 51. A method for communicating between a first site behind a
2 first firewall and a second site behind a second
3 firewall, comprising:
4 informing the second site about a port on the first
5 firewall;
6 transmitting a first data packet addressed to the port on
7 the first firewall from the second site through a
8 port on the second firewall;
9 relaying the first data packet to the first site in
10 response to the first firewall being promiscuous;
11 transmitting a second data packet addressed to the port
12 on the second firewall from the first site through
13 the port on the first firewall; and
14 relaying the second data packet to the second site.

1 52. The method of claim 51, wherein informing the second site
2 about a port on the first firewall further includes:
3 establishing a first link between the first site and an
4 external site through the port on the first
5 firewall;
6 establishing a second link between the second site and
7 the external site through the second firewall; and
8 transmitting a message from the external source to the
9 second site identifying the port on the first
10 firewall.

WO 03/039053

PCT/US02/35285

1 53. The method of claim 52, wherein establishing a first link
2 between the first site and an external site through the
3 port on the first firewall and establishing a second link
4 between the second site and the external site through the
5 second firewall further include:
6 transmitting a first initializing data packet from the
7 first site to the external site through the port on
8 the first firewall; and
9 transmitting a second initializing data packet from the
10 second site to the external site through the second
11 firewall.

1 54. The method of claim 51, further comprising identifying
2 the first firewall as promiscuous.

1 55. The method of claim 54, wherein identifying the first
2 firewall includes:
3 transmitting an outgoing data packet from the first site
4 to the external site through the port on the first
5 firewall;
6 informing a second external site about the port on the
7 first firewall, the second external site having a
8 different network address from the first external
9 site;
10 transmitting an incoming data packet addressed to the
11 port on the first firewall from the second external
12 site; and
13 identifying the first firewall as being promiscuous in
14 response to the first site receiving the incoming
15 data packet.

WO 03/039053

PCT/US02/35285

1 56. A method for communicating between a first site behind a
2 first firewall and a second site behind a second
3 firewall, comprising:
4 informing the first site about the second firewall;
5 informing the second site about a port on the first
6 firewall;
7 transmitting a first data packet addressed to the second
8 firewall through the port on the first firewall;
9 transmitting a second data packet addressed to the port
10 on the first firewall from the second site through
11 a port on the second firewall;
12 relaying the second data packet to the first site in
13 response to the first firewall being non-strict;
14 transmitting a third data packet addressed to the port on
15 the second firewall from the first site through the
16 port on the first firewall; and
17 relaying the third data packet to the second site.

1 57. The method of claim 56, wherein informing the first site
2 about the second firewall and informing the second site
3 about a port on the first firewall further include:
4 establishing a first link between the first site and an
5 external site through the port on the first
6 firewall and a second link between the second site
7 and the external site through the second firewall;
8 transmitting a first message from the external source to
9 the first site identifying the second firewall; and
10 transmitting a second message from the external source to
11 the second site identifying the port on the first
12 firewall.

WO 03/039053

PCT/US02/35285

1 58. The method of claim 57, wherein establishing a first link
2 between the first site and an external site through the
3 port on the first firewall and a second link between the
4 second site and the external site through the second
5 firewall further includes:
6 transmitting a first initializing data packet from the
7 first site to the external site through the port on
8 the first firewall; and
9 transmitting a second initializing data packet from the
10 second site to the external site through the second
11 firewall.

1 59. The method of claim 56, further comprising identifying
2 the first firewall as non-strict.

1 60. The method of claim 59, wherein identifying the first
2 firewall includes:
3 transmitting an outgoing data packet from the first site
4 to a first port of the external site through the
5 port on the first firewall;
6 transmitting an incoming data packet addressed to the
7 port on the first firewall from a second port on
8 the external source, the second port being
9 different from the first port; and
10 identifying the first firewall as being non-strict in
11 response to the first site receiving the incoming
12 data packet.

WO 03/039053

1/11

PCT/US02/35285





FIG. 1

WO 03/039053

2/11

PCT/US02/35285



200


FIG. 2

SUBSTITUTE SHEET (RULE 26)

WO 03/039053

3/11

PCT/US02/35285



300

FIG. 3

WO 03/039053

4/11

PCT/US02/35285





FIG. 4

WO 03/039053


5/11

PCT/US02/35285




500

FIG. 5A



500

FIG. 5B




500

FIG. 5C

WO 03/039053

6/11

PCT/US02/35285



600


Fig. 6

SIIRATITITE SHEET (DIII F 2A)

WO 03/039053

7/11

PCT/US02/35285




700
FIG. 7

WO 03/039053

8/11

PCT/US02/35285




800
FIG. 8A

WO 03/039053

9/11


PCT/US02/35285



WO 03/039053

10/11


PCT/US02/35285



WO 03/039053

11/11

PCT/US02/35285



900

FIG. 9

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.